




















USB3 Type #4

- for medium load requirements
- PUR outer jacket
- shielded
- oil-resistant and coolant-resistant
- notch-resistant
- PVC-free/halogen-free
- flame-retardant
- hydrolysis-resistant and microbe-resistant

	Conductor	Stranded conductor in especially bending-resistant version consisting of bare copper wires (following EN 60228).
	Core insulation	According to bus specification.
	Core stranding	According to bus specification.
	Core identification	According to bus specification ▶ Schedule delivery program
	Overall shield	Bending-resistant braiding made of tinned copper wires. Coverage approx. 55% linear, approx. 80% optical.
	Outer jacket	Low-adhesion, highly abrasion-resistant mixture on the basis of PUR, adapted to suit the requirements in energy chains* (following DIN VDE 0282 Part 10). Colour: Red lilac (similar to RAL 4001)
	Bending radius	moved minimum 12,5 x d fixed minimum 7,5 x d
	Temperature	moved -20 °C to +70 °C fixed -40 °C to +70 °C
	v max. unsupported/gliding	3 m/s, 2 m/s
	a max.	30 m/s ²
	Travel distance	Freely suspended travel distances and up to 20 m for gliding applications, Class 2
	UV-resistant	Medium
	Nominal voltage	50 V
	Testing voltage	500 V
	Oil	Oil-resistant (following DIN EN 50363-10-2), Class 3.
	Offshore	MUD-resistant following NEK 606 – status 2009.
	Flame-retardant	According to IEC 60332-1-2, CEI 20-35, FT1, WW-1
	Silicon-free	Free from silicon which can affect paint adhesion (following PV 3.10.7 – status 1992).
	Halogen-free	Following EN 50267-2-1.

	UL/CSA	Style 1598 and 20236, 30 V, 80 °C
	NFPA	Following NFPA 79-2012 chapter 12.9
	CEI	Following CEI 20-35
	CE	Following 2006/95/EG
	DESINA	According to VDW, DESINA standardisation
	Lead free	Following 2011/65/EC (RoHS-II)
	Clean room	According to ISO Class 1. Outer jacket material complies with CF77.UL.05.12.D, tested by IPA according to standard 14644-1
	CTP	Certified according to N° C-DE.PB49.V.00396
	EAC	Certified according to N° TC RU C-DE.ME77.B.00963

New! Guaranteed lifetime for this series according to the "chainflex® guarantee club" conditions ▶ Page 22-25

Double strokes*	v max. [m/s]	a max. [m/s ²]	Travel distance [m]	5 million R min. [factor x d]	7,5 million R min. [factor x d]	10 million R min. [factor x d]
Temperature, from/to [°C]	unsupported	gliding				
-20 / -10			30	≤20	15	16
-10 / +60	3	2			12,5	13,5
+60 / +70					15	16

* higher number of double strokes possible

Typical application area

- for medium load requirements
- almost unlimited resistance to oil
- indoor and outdoor applications without direct sun radiation
- freely suspended travel distances and up to 20 m for gliding applications
- Bus connection cable for machining units/machine tools, low-temperature applications

Delivery program Part No.	Number of cores and conductor nominal cross section [mm ²]	External diameter max. [mm]	Copper index [kg/km]	Weight [kg/km]	Delivery program Part No.	Characteristic wave impedance approx. [Ω]	Core group	Colour code
Profibus					Profibus			
CFBUS.PUR.001	(2x0,25)C	8,5	27	74	CFBUS.PUR.001	150	(2x0,25)C	red, green
CAN-Bus					CAN-Bus			
CFBUS.PUR.021	(2x0,5)C	8,5	33	83	CFBUS.PUR.021	120	(2x0,5)C	white, brown
CFBUS.PUR.022 ²⁰	(4x0,5)C	8,5	46	93	CFBUS.PUR.022 ²⁰	120	(4x0,5)C	white, green, brown, yellow (star-quad stranding)
Ethernet/CAT5/GigE					Ethernet/CAT5/GigE			
CFBUS.PUR.040 ²⁰	(4x0,25)C	6,5	30	68	CFBUS.PUR.040 ²⁰	100	(4x0,25)C	white, green, brown, yellow (star-quad stranding)
CFBUS.PUR.045	(4x(2x0,15))C	7,5	35	68	CFBUS.PUR.045	100	(4x(2x0,15))C	white-blue/blue, white-orange/orange, white-green/green, white-brown/brown
Ethernet/CAT6_A					Ethernet/CAT6_A			
CFBUS.PUR.050	4x(2x0,20)C	9,5	69	122	CFBUS.PUR.050	100	4x(2x0,20)C	white/blue, white/orange, white/green, white/brown
FireWire IEEE 1394b					FireWire IEEE 1394b			
CFBUS.PUR.056	(2x(2x0,15)C+2x0,38)C	9,0	62	94	CFBUS.PUR.056	100	(2x(2x0,15)C+2x0,38)	orange/blue, blue/red, black, white
Profinet					Profinet			
CFBUS.PUR.060 ^{20/16}	(4x0,38)C	7,0	35	66	CFBUS.PUR.060 ^{20/16}	100	(4x0,38)C	white, orange, blue, yellow (star-quad stranding)
USB 3.0					USB 3.0			
CFBUS.PUR.068	(2x(2xAWG28)+2x(2xAWG28)C)C	7,0	41	66	CFBUS.PUR.068	90	2x(2xAWG28)+2x(2xAWG28)C	red/black, green/white-green, blue/yellow, red/fioletowy