

PATCH PANEL MODEL PF 20097

32 PORT ASYNC OCTAL PATCH PANEL

Description:

The 32 Port ASYNC Octal Patch Panel interfaces banks of 8 RJ45 connectors on the front of the panel to four SCSI 68 position connectors on the rear. The panel is designed to work with Cisco® Asynchronous Network Models NM-16A and NM-32A, which are utilized on Cisco® 2600, 3620/40, and 3660 series routers. The PF 20097 Patch Panel replaces 4 CAB-OCTAL-ASYNC cables. Interface cables are available in a variety of lengths.

Dimensions:

Benefits:

- Replaces:4 CAB-OCTAL-ASYNC cables
- PCB internal construction
- External stainless steel construction
- Cleaner wire management
- Economical solution
- Occupies only 1 rack unit

Specifications:

- P/N: PF 20097
- Patented: #6,302,742 B1
- EIA-310-D Compliant
- Built-in strain relief
- Fully enclosed unit
- 2 year warranty



PF 20097 Requires (4 ea.) "PF 20091-XX" interface cables for full 32 port utilization

XX = Length designator in FT

(4' and 6' are standard stocked lengths)





PATCH PANEL MODEL PF 20097

32 PORT ASYNC OCTAL PATCH PANEL

Port Map:

Torr map.	
NM16A/	PF 20097
NM 32A	RJ-45 Port
0	1
1	2
2	3
3	4
4	5
5	6
6	7
7	8
8	9
9	10
10	11
11	12
12	13
13	14
14	15
15	16
NM 32A	PF 20097 RJ-45 Port
NM 32A 16	
	RJ-45 Port
16	RJ-45 Port 17
<u>16</u> 17	RJ-45 Port 17 18
16 17 18	RJ-45 Port 17 18 19
16 17 18 19	RJ-45 Port 17 18 19 20
16 17 18 19 20	RJ-45 Port 17 18 19 20 21
16 17 18 19 20 21	RJ-45 Port 17 18 19 20 21 22
16 17 18 19 20 21 22	RJ-45 Port 17 18 19 20 21 22 23
16 17 18 19 20 21 22	RJ-45 Port 17 18 19 20 21 22 23
16 17 18 19 20 21 22 23	RJ-45 Port 17 18 19 20 21 22 23 24
16 17 18 19 20 21 22 23	RJ-45 Port 17 18 19 20 21 22 23 24
16 17 18 19 20 21 22 23 24 25	RJ-45 Port 17 18 19 20 21 22 23 24 25 26
16 17 18 19 20 21 22 23 24 25 26	RJ-45 Port 17 18 19 20 21 22 23 24 25 26 27
16 17 18 19 20 21 22 23 24 25 26 27	RJ-45 Port 17 18 19 20 21 22 23 24 25 26 27 28
16 17 18 19 20 21 22 23 24 25 26 27 28	RJ-45 Port 17 18 19 20 21 22 23 24 25 26 27 28
16 17 18 19 20 21 22 23 24 25 26 27 28 29	RJ-45 Port 17 18 19 20 21 22 23 24 25 26 27 28 29 30

Other Specifications:

RoHS Compliant

• Operating Temperature32 to 104°F (0 to 40°C)

• Storage temperature-40 to 167°F (-40 to 75°C)

• Alarm capableNo

C.L.E.I. Code:

Product Code = COMW310GRA Mfg. Code = CPXP



COMMON LANGUAGE and Telcordia are registered trademarks and CLEI is a trademark of Telcordia Technologies, Inc.

Signal Assignment:

Pin #	Signal
8	RTS
7	DTR
6	TXC
5	TXC GND
4	RXC GND
3	RXC
2	DSR
1	CTS

Warranty:

Components Express, Inc. warrants that all goods furnished will be free from defects in material and workmanship, conform to all applicable specifications, drawings, samples, and descriptions, and unless of Purchaser's own design, will be free from design defects. Components Express, Inc. further warrants that all services performed will be free from defects in workmanship and materials, and comply with all applicable laws, rules and regulations and all specifications, descriptions, and drawings. All warranties shall run to Purchaser and its customers for a period of 2 years from the date of purchase by the end customer. THE WARRANTIES SET FORTH IN THIS PARAGRAPH ARE EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS AND IMPLIED WARRANTIES INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.